








序号	品名	材质
①	0.5拉接胶芯 (H1.2)	LCP UL94V-0 本色
②	0.5拉接下端子 (H1.2)	磷青铜/表面镀锡 镀金
③	0.5拉接后盖 (H1.2)	LCP UL94V-0 黑色
④	0.5拉接焊片 (H1.2)	磷青铜/表面镀锡



1. MATERIAL
HOUSING: LCP UL94V-0
ACTIVATOR: LCP UL94V-0
CONTACTS: COPPER ALLOY
PEG: COPPER ALLOY
2. PLATING:
CONTACTS: TIN OVER NICKEL
PEG: TIN OVER NICKEL
3. PART NO:
OPERATING VOLTAGE: 50V AC, DC
CURRENT RATING: 0.3A AC, DC
OPERATING TEMPERATURE: -25°C ~ +85°C

CKT	DIM A	DIM B	DIM C
4	1.50	2.56	7.96
5	2.00	3.06	8.46
6	2.50	3.56	8.96
7	3.00	4.06	9.46
8	3.50	4.56	9.96
9	4.00	5.06	10.46
10	4.50	5.56	10.96
11	5.00	6.06	11.46
12	5.50	6.56	11.96
13	6.00	7.06	12.46
14	6.50	7.56	12.96
15	7.00	8.06	13.46
16	7.50	8.56	13.96
17	8.00	9.06	14.46
18	8.50	9.56	14.96
19	9.00	10.06	15.46
20	9.50	10.56	15.96
21	10.00	11.06	16.46
22	10.50	11.56	16.96
23	11.00	12.06	17.46
24	11.50	12.56	17.96
25	12.00	13.06	18.46
26	12.50	13.56	18.96
27	13.00	14.06	19.46
28	13.50	14.56	19.96
29	14.00	15.06	20.46
30	14.50	15.56	20.96
31	15.00	16.06	21.46
32	15.50	16.56	21.96

CKT	DIM A	DIM B	DIM C
33	16.00	17.06	22.46
34	16.50	17.56	22.96
35	17.00	18.06	23.46
36	17.50	18.56	23.96
37	18.00	19.06	24.46
38	18.50	19.56	24.96
39	19.00	20.06	25.46
40	19.50	20.56	25.96
41	20.00	21.06	26.46
42	20.50	21.56	26.96
43	21.00	22.06	27.46
44	21.50	22.56	27.96
45	22.00	23.06	28.46
46	22.50	23.56	28.96
47	23.00	24.06	29.46
48	23.50	24.56	29.96
49	24.00	25.06	30.46
50	24.50	25.56	30.96
51	25.00	26.06	31.46
52	25.50	26.56	31.96
53	26.00	27.06	32.46
54	26.50	27.56	32.96
55	27.00	28.06	33.46
56	27.50	28.56	33.96
57	28.00	29.06	34.46
58	28.50	29.56	34.96
59	29.00	30.06	35.46
60	29.50	30.56	35.96

UNITS	FINISH
mm	
MATL	
X ± 0.3	X ± 5'
X ± 0.25	X ± 2'
X ± 0.20	X ± 1'
XXX ± 0.10	XXX ± 0.5'

QTY	PCS

UNITS	DR
mm	HU 2016.09.28

QWYCONN 深圳市启威源电子有限公司
SHENZHEN QIWEIYUAN ELECTRONIC CO., LTD.

TITLE: 0.5 Pitch拉接卧式下接 (H=1.2)

APPD: 0512-XXRL-SN

CHKD:

DWG NO.: 0512-XXRL-SN

SCALE: 1/1

SHEET: 1/1

REV: A