



Note:  
 RATED VOLTAGE(MAX):220V  
 RATED CURRENT(MAX):2.0A  
 AMBIENT TEMPERATURE RANGE:-20 °C~+85 °C  
 CONTACT RESISTANCE:20mΩMAX  
 INSULATION RESISTANCE:1000MΩMIN  
 HOUSING: PA9T UL94V-0  
 CONTACT: PHOSPHOR BRONZE TIN-LEAD PLATED

极数	尺寸	
	A	B
1.25T-2PW	1.25	4.35
1.25T-3PW	2.50	5.60
1.25T-4PW	3.75	6.85
1.25T-5PW	5.00	8.10
1.25T-6PW	6.25	9.35
1.25T-7PW	7.50	10.60
1.25T-8PW	8.75	11.85
1.25T-9PW	10.00	13.10
1.25T-10PW	11.25	14.35
1.25T-11PW	12.50	15.60
1.25T-12PW	13.75	16.85
1.25T-13PW	15.00	18.10
1.25T-14PW	16.25	19.35
1.25T-15PW	17.50	20.60
1.25T-16PW	18.75	21.85

UNITS mm	<b>QWYCONN</b> 深圳市启崴源电子有限公司 SHENZHEN QIWEIYUAN ELECTRONIC CO., LTD.		
MAT'L	PART NO.(INTENDED USE) 1.25T-nPW	TITLE: 1.25弯针针座	
FINISH	APPD:	DWG NO.: 1.25T-nPW	
Q'TY PCS	CHKD:	DR: HU 2016.09.28	SCALE 1/1
			SHEET 1/1
			REV. A

X.± 0.3	X° ± 5°
.X± 0.25	.X° ± 2°
.XX± 0.20	.XX° ± 1°
.XXX± 0.10	.XXX° ± 0.5°