



技术要求

1. 塑件表面应光洁, 无毛刺, 明显收缩, 缺陷, 裂纹等现象;
2. 插针表面电镀应光亮, 无斑纹, 划痕;
3. 未注公差按SJ1372-79中7级;
4. 温度范围: -25℃ 85℃;
5. 额定电压: 250V, AC, DC;
6. 接触电阻: ≤0.01 Ω;
7. 绝缘电阻: ≥1000m Ω;
8. 耐压: 1500V, AC/minute

UNITS mm	QWYCONN ® 深圳市启崴源电子有限公司 SHENZHEN QIWEIYUAN ELECTRONIC CO., LTD.								
MAT'L	PART NO.(INTENDED USE) BH3.5-2PK	TITLE: 3.5-2P高压插座带扣							
FINISH	APPD:	DWG NO.: BH3.5-2P带扣							
Q'TY PCS	CHKD:	DR: HU 2016.09.28	<table border="1"> <tr> <td>SCALE</td> <td>SHEET</td> <td>REV.</td> </tr> <tr> <td>1/1</td> <td>1/1</td> <td>A</td> </tr> </table>	SCALE	SHEET	REV.	1/1	1/1	A
SCALE	SHEET	REV.							
1/1	1/1	A							

X. ± 0.3	X° ± 5°
.X ± 0.25	.X° ± 2°
.XX ± 0.20	.XX° ± 1°
.XXX ± 0.10	.XXX° ± 0.5°

