



主要技术参数 Main Specifications

- 线数 (Poles): 02 to 16
- 接触电阻 (Contact resistance): $\leq 20\text{m}\Omega$
- 绝缘电阻 (Insulation resistance): $\geq 100\text{M}\Omega$
- 额定电压 (Rated voltage): 125 V AC DC
- 额定电流 (Rated current): 1.0A AC DC
- 耐电压 (Withstand Voltage): 500V AC/minute
- 温度范围 (Temperature Range): $-25^{\circ}\text{C} \sim +105^{\circ}\text{C}$

NO.	DESCRIPTION	QTY	MATERIAL	PLATING/COLOR
A	Insulator	1	LCP (UL94V-0)	Beige
B	Contacts	2	PhosphorBronze	Tin-plated
C	Solder Tab	2	PhosphorBronze	Tin-plated

SUGGESTED PCB LAYOUT (COMPONENT SIDE)

X.± 0.3	X°± 5°
.X± 0.25	.X°± 2°
.XX± 0.20	.XX°± 1°
.XXX± 0.10	.XXX°± 0.5°

UNITS	深圳市启崴源电子有限公司		
mm	SHENZHEN QIWEIYUAN ELECTRONIC CO., LTD.		
MAT'L	PART NO.(INTENDED USE)	TITLE:	
	A1252AWR-nPWB	1.25 卧贴针座窄焊片	
FINISH	APPD:	DWG NO.:	
		A1252AWR-nPWB	
Q'TY	CHKD:		SCALE
PCS	DR: HU 2016.09.28		SHEET
			REV.
		1/1	1/1
			A