



NOTES1:

UL Standard

1. Use group	B	C	D
Rated Current	20A	20A	10A
Rated Voltage	300V	300V	300V

2. Torque value: M4, 10.53Lb.in

3. Wire range: 22~10AWG

IEC Standard

1. Pollution Degree	3	2	2
Overtoltage Category	III	III	II
Rate Impulse Voltage(KV)	/	6	/
Rate Voltage(V)	/	400V	/
Rate Current(A)	/	17.5A	/

2. Torque value: M4, 1.2Nm

3. wire range: 0.5-4.0mm²

NOTES2:

1. Housing: PA66(UL94V-0)

2. Solder Pin: Brass(Sn Plated)

3. Screw: Steel(M4, Ni Plated)

4. Cover: PC

NOTES3:

1. Pitch: 9.50mm Poles: 02-24P

2. Operating temperature: -40℃~+105℃

3. RoHS Compliance

How to order

HB9500 - G - 9.5 - XXXX - XXP - X - X - X

产品型号 间距 颜色: 极数 A-Z其他定制

灰色:GY 蓝色:BU 黑色:BK 绿色:GN 透明色:TT 白色:WE

橙色:OE 红色:RD 透明色:TT 白色:WE

定制颜色

01:常规颜色 0:Y一字螺丝 1:S十字螺丝 CU:铜方块 2:PS平头十字螺丝 FE:铁方块

Pitch Range In mm			Nominal Dimension Range In mm					- \cap \square
TO	Over	Over	TO	Over	Over	Over	0.1/10	
6	10	24	30	60	100	150	\angle	
± 0.15	± 0.20	± 0.30	± 0.30	± 0.50	± 0.70	± 1.00	$\pm 2^\circ$	

DESIGN:	Xiping Huang	QWYCONN® 深圳市启崴源电子有限公司			
CHECK:	Ke Tian	SHENZHEN QIWEIYUAN ELECTRONIC CO., LTD.			
APPROVED:	Yuanquan Xu	TITLE: HB9500G-9.5-XXP			
DIM	TOL	DIM	TOL	PART NO.	
X.	± 0.25	X°	$\pm 3.0^\circ$	REV. A	
X.X	± 0.20	X.X°		SCALE: N/A	UNIT: mm
X.XX	± 0.15	X.XX°		SHEET: 1/1	
X.XXX		X.XXX°			